

Enough `java.lang.String` to Hang Ourselves ...

Dr Heinz M. Kabutz, Dmitry Vyazelenko

Last updated: 2020-07-30



Javaspecialists.eu
java training

Which do you think is fastest?

```
String appendBasic(String question, String answer1, String answer2) {  
    return "<h1>" + question + "</h1><ol><li>" + answer1 +  
        "</li><li>" + answer2 + "</li></ol>";  
}  
  
String appendStringBuilder(String question, String answer1, String answer2) {  
    return new StringBuilder().append("<h1>").append(question)  
        .append("</h1><ol><li>").append(answer1)  
        .append("</li><li>").append(answer2)  
        .append("</li></ol>").toString();  
}  
  
String appendStringBuilderSize(String question, String answer1, String answer2) {  
    int len = 36 + question.length() + answer1.length() + answer2.length();  
    return new StringBuilder(len).append("<h1>").append(question)  
        .append("</h1><ol><li>").append(answer1)  
        .append("</li><li>").append(answer2)  
        .append("</li></ol>").toString();  
}
```

When the Dinosaurs Roamed the Earth - Java 1.0

- **Fields:**
 - `private char value[];`
 - `private int offset;`
 - `private int count;`
- `hashCode()` used samples of chars if String was longer than 16
- `equals()` did not check if `obj == this`
- `intern()` used a static Hashtable
 - Memory Leak
- `StringBuffer` a modifiable, thread-safe version
 - `toString()` shared the underlying `char[]` unless it was later modified

hashCode() in String 1.0

```
public int hashCode() {  
    int h = 0;  
    int off = offset;  
    char val[] = value;  
    int len = count;  
  
    if (len < 16) {  
        for (int i = len ; i > 0; i--) {  
            h = (h * 37) + val[off++];  
        }  
    } else {  
        // only sample some characters  
        int skip = len / 8;  
        for (int i = len ; i > 0; i -= skip, off += skip) {  
            h = (h * 39) + val[off];  
        }  
    }  
    return h;  
}
```

Who's Who

- **Dmitry Vyazelenko @DVyazelenko**
 - Principal Consultant, Safepoint Ost GmbH
 - JCrete Chief Disorganizer
 - www.jcrete.org
- **Heinz Kabutz @heinzkabutz**
 - Java Specialists Newsletter
 - www.javaspecialists.eu

tinyurl.com/nisjug20

Early Hunter Gatherer - Java 1.1

- Fields stayed the same
- `hashCode()` still sampling
- `intern()` moved to native code
 - Not necessarily better than Java
- `toUpperCase()` added some weird edge cases such as ß → SS

tinyurl.com/nisjug20

Discovering Fire - Java 1.2

- Fields still the same
- `hashCode()` changed to

```
public int hashCode() {  
    int h = 0;  
    int off = offset;  
    char val[] = value;  
    int len = count;  
  
    for (int i = 0; i < len; i++)  
        h = 31*h + val[off++];  
  
    return h;  
}
```

- Broke a bunch of code

tinyurl.com/nisjug20


- Introduced the Comparable interface

Old Hash vs New Hash Calculation Performance

- Java 1.0 and 1.1 calculation was $O(1)$ - constant time
- Java 1.2 calculation is $O(n)$ - linear time

Java 2 Performance and Idiom Guide

- Proposed wrapping `String` with own object and caching hash code



Stone Age - Java 1.3

- **Fields:**

- **private char value[];**
- **private int offset;**
- **private int count;**
- **private int hash; ←**

```
public int hashCode() {  
    int h = hash;  
    if (h == 0) {  
        int off = offset;  
        char val[] = value;  
        int len = count;  
  
        for (int i = 0; i < len; i++)  
            h = 31*h + val[off++];  
        hash = h;  
    }  
    return h;  
}
```

Some guys from Serbia ...

"ARbyguv", "ARbygvW", "ARbyhVv", "ARbyhWW", "ARbzHuv", "ARbzHvW", "ARbzIVv", "ARbzIW",
"ARcZgув", "ARcZgvW", "ARcZhVv", "ARcZhWW", "ASCyгуv", "ASCygvW", "ASCyhVv", "ASCyhWW",
"ASCzHuv", "ASCzHvW", "ASCzIVv", "ASCzIW", "ASDZгуv", "ASDZgvW", "ASDZhVv", "ASDZhWW",
"bmгkAEs", "bmгkAFT", "bmhLAEs", "bmhLAFT", "bnHkAEs", "bnHkAFT", "bnILAЕs", "bnILAFT",
"cNгkAEs", "cNгkAFT", "cNhLAEs", "cNhLAFT", "c0HkAEs", "c0HkAFT", "c0ILAЕs", "c0ILAFT",
"Elcnfnz", "Elcng0z", "ElcoGnz", "ElcoH0z", "Eld0fnz", "Eld0g0z", "EldPGnz", "EldPH0z",
"EmDnfnz", "EmDng0z", "EmDoGnz", "EmDoH0z", "EmE0fnz", "EmE0g0z", "EmEPGnz", "EmEPH0z",
"FMcnfnz", "FMcng0z", "FMcoGnz", "FMcoH0z", "FMd0fnz", "FMd0g0z", "FMdPGnz", "FMdPH0z",
"FNDnfnz", "FNDng0z", "FNDoGnz", "FNDoH0z", "FNE0fnz", "FNE0g0z", "FNEPGnz", "FNEPH0z",
"Obdw dac", "ObdwdbD", "ObdweBc", "ObdweCD", "ObdxEac", "ObdxEbD", "ObdxFBc", "ObdxFCD",
"Obex dac", "ObexdbD", "ObexeBc", "ObexeCD", "ObeyEac", "ObeyEbD", "ObeyFBc", "ObeyFCD",
"OcEwdac", "OcEwdbD", "OcEweBc", "OcEweCD", "OcExEac", "OcExEbD", "OcExFBc", "OcExFCD",
"OcFXdac", "OcFXdbD", "OcFXeBc", "OcFXeCD", "OcFYEac", "OcFYEbD", "OcFYFBc", "OcFYFCD",
"PCdwdac", "PCdwdbD", "PCdweBc", "PCdweCD", "PCdxEac", "PCdxEbD", "PCdxFBc", "PCdxFCD",
"PCeXdac", "PCeXdbD", "PCeXeBc", "PCeXeCD", "PCeYEac", "PCeYEbD", "PCeYFBc", "PCeYFCD",
"PDEwdac", "PDEwdbD", "PDEweBc", "PDEweCD", "PDExEac", "PDExEbD", "PDExFBc", "PDExFCD",
"PDFXdac", "PDFXdbD", "PDFXeBc", "PDFXeCD", "PDFYEac", "PDFYEbD", "PDFYFBc", "PDFYFCD",
"Xwfaark", "XwfaasL", "XwfabSk", "XwfabTL", "XwfbBrk", "XwfbBsL", "XwfbCSk", "XwfbCTL",
"XwgBark", "XwgBasL", "XwgBbSk", "XwgBbTL", "XwgCBrk", "XwgCBsL", "XwgCCSk", "XwgCCTL",
"XxGaark", "XxGaasL", "XxGabSk", "XxGabTL", "XxGbBrk", "XxGbBsL", "XxGbCSk", "XxGbCTL",
"XxHBark", "XxHBasL", "XxHBbSk", "XxHBbTL", "XxHCBrk", "XxHCBsL", "XxHCCSk", "XxHCCTL",
"zsjpxah", "zsjpxbI", "zsjpyBh", "zsjpyCI", "zsjqYah", "zsjqYbI", "zsjqZBh", "zsjqZCI",

All Those Strings Have `hashCode() == 0`

- Plus any combination of these Strings also have `hashCode` of 0
 - Thus we can produce an endless sequence of such Strings
 - `"zsjpyClcOHkAEsObeXeCDASCzIVv".hashCode() == 0`
- Why is this so bad?
- github.com/kabutz/string-performance
 - `eu.javaspecialists.playground.hasher.StringDOS`

StringDOS Demo Java 6



Javaspecialists.eu
java training

Bucket Collisions

- Can attack server by sending lots of Strings with same hashCode
 - Very easy to do when == 0
- Both `put()` and `get()` become linear

Brief History Lesson of String - Java 1.4

- Fields same as 1.3
- Introduced CharSequence interface
- Regular expressions
 - Methods like `matches()`, `split()`, etc.

Before we go on ...

- Adding Strings together

```
public class Hello {  
    public static void main(String[] args) {  
        System.out.println("Hello " + args[0]);  
    }  
}
```

- Became (Java 1.0 - 1.4)

```
public class Hello {  
    public static void main(String[] args) {  
        System.out.println(new StringBuffer().append("Hello ")  
            .append(args[0]).toString());  
    }  
}
```

- `new StringBuffer()` would create an array of 16 characters

Brief History Lesson of String - Java 1.5

- Fields same as 1.3, but marked final (except for hash)
- Code points introduced
 - 32-bit characters
- `StringBuilder` as unsynchronized `StringBuffer`
 - `char[]` no longer shared with created `Strings`
- Needed to recompile all code
 - And hand-crafted `StringBuffer` code would now typically be slower than +

Brief History Lesson of String - Java 1.6

- Not much changed since 1.5
- **-XX:+UseCompressedStrings**
 - `byte[]` when 7-bit ASCII
 - otherwise `char[]`
- **-XX:+OptimizeStringConcat**
 - `char[]` could in some cases be shared between `StringBuilder/Buffer` and `String`

Quiz 2: StringAppenderBenchmark.append Strings

	1.6.0_113	1.7.0_191	1.8.0_172	11
appendBasic	61 ns/op 208 B/op	56 ns/op 200 B/op	58 ns/op 200 B/op	75 ns/op 120 B/op
appendString Builder	61 ns/op 208 B/op	56 ns/op 200 B/op	58 ns/op 200 B/op	75 ns/op 120 B/op
appendString BuilderSize	57 ns/op 208 B/op	57 ns/op 200 B/op	58 ns/op 200 B/op	75 ns/op 120 B/op

Brief History Lesson of String - Java 1.7

- **Fields:**
 - `private final char value[];`
 - `private int hash;`
 - `private transient int hash32 = 0; // used to avoid DOS attacks on HashMap`
- **new constructor `String(char[], boolean unshared)`**
 - `SharedSecrets.getJavaLangAccess().newStringUnsafe(char[])`
 - Moved out of harm's way since Java 9
- **`String.substring()` now created new `char[]`s**
 - `SubbableString` alternative
 - Newsletter 230 - <https://www.javaspecialists.eu/archive/Issue230.html>

StringDOS Demo Java 7

-Djdk.map.althashing.threshold=512



Javaspecialists.eu
java training

Brief History Lesson of String - Java 1.8

- **Fields:**
 - `private final char value[];`
 - `private int hash;`
- **static methods for joining several Strings**
- **Deduplication of `char[]`s**
- **Hash Maps use trees in case of too many bucket collisions**

String Deduplication www.javaspecialists.eu/archive/Issue270.html

- Java 1.8.0_20 can replace `char[]`s of duplicate strings

- Only works for the G1 collector `-XX:+UseStringDeduplication`
- Threshold when deduplicated `-XX:StringDeduplicationAgeThreshold`

```
public class DeduplicationDemo {  
    public static void main(String... args) throws Exception {  
        char[] heinz = {'h', 'e', 'i', 'n', 'z'};  
        String[] s = {new String(heinz), new String(heinz),};  
        Field value = String.class.getDeclaredField("value");  
        value.setAccessible(true);  
        System.out.println("Before GC");  
        System.out.println(value.get(s[0]));  
        System.out.println(value.get(s[1]));  
        System.gc(); Thread.sleep(100);  
        System.out.println("After GC");  
        System.out.println(value.get(s[0]));  
        System.out.println(value.get(s[1]));  
    }  
}
```

Before GC
[C@76ed5528
[C@2c7b84de
After GC
[C@2c7b84de
[C@2c7b84de

Deduplication vs `intern()` vs Roll Own

- **`new String("Hello World!")` in Java 8 64-bit compressed OOPS**
 - `String`: 12 (header) + 4 (value) + 4 (hash) \approx 24 bytes
 - `char[]`: 12 (header) + 24 (12 characters) + 4 (length) = 40 bytes
 - Total: 64 bytes
- **Deduplication saves 40 bytes automagically**
- **`intern()` saves 64 bytes, but at high cost**
 - Until Java 10, intern table did not grow
 - `jcmd` in Java 9+ can show details with `VM.stringtable`
- **Own ConcurrentHashMap with `putIfAbsent(s, s)` saves 64 bytes**
 - But potential memory leak as unused Strings never deleted

StringDOS Demo Java 8



Javaspecialists.eu
java training

Brief History Lesson of String - Java 9 / 10 / 11 / 12

- **Fields:**

- **private final byte[] value;**
- **private final byte coder;**
- **private int hash;**

Indify String Concatenation Java 9+

- **+ is no longer compiled to StringBuilder**
 - `StringConcatFactory`
 - Demo and look at benchmarks: <https://github.com/kabutz/string-performance>

StringAppenderBenchmark Mixed Parameters

	1.6.0_113	1.7.0_191	1.8.0_172	11
plus	319 ns/op 896 B/op	317 ns/op 864 B/op	333 ns/op 864 B/op	127 ns/op 152 B/op
sb_sized	220 ns/op 536 B/op	230 ns/op 504 B/op	245 ns/op 504 B/op	259 ns/op 280 B/op
sb	320 ns/op 896 B/op	316 ns/op 864 B/op	332 ns/op 864 B/op	303 ns/op 488 B/op
concat	644 ns/op 2024 B/op	576 ns/op 1712 B/op	590 ns/op 1664 B/op	368 ns/op 960 B/op
format	4088 ns/op 3560 B/op	3541 ns/op 3504 B/op	3208 ns/op 3304 B/op	3855 ns/op 1896 B/op

JEP 280: Indify String Concatenation

- **Uses invokedynamic for String concatenation**
- **Bytecode generator**
 - `BC_SB` - like old Java 5 + concatenation
 - `BC_SB_SIZED`
 - `BC_SB_SIZED_EXACT`
- **MethodHandles**
 - `MH_SB_SIZED`
 - `MH_SB_SIZED_EXACT`
 - `MH_INLINE_SIZED_EXACT` (default)
 - Converts non-primitives, float and double to `String` using `StringifierMost`
 - Uses `StringConcatHelper#mixLen` to compute exact sizes for other primitives

StringAppenderBenchmark.plus

- `-Djava.lang.invoke.stringConcat=...`

	plus with mixed values
MH_INLINE_SIZED_EXACT	127 ns/op, 152 B/op
BC_SB_SIZED_EXACT	157 ns/op, 208 B/op
MH_SB_SIZED	251 ns/op, 328 B/op
BC_SB_SIZED	255 ns/op, 328 B/op
MH_SB_SIZED_EXACT	290 ns/op, 408 B/op
BC_SB	301 ns/op, 512 B/op

JEP 254: Compact Strings

- **char[] replaced with byte[]**
- **Saves space if characters fit into a byte (i.e. Latin1)**
- **kill switch -XX:-CompactStrings**
- **Max String length is now half of what it was**
 - Whether compact Strings disabled or not Latin1 String

StringAppenderBenchmark +/- CompactStrings

	+CompactStrings	-CompactStrings
plus	127 ns/op, 152 B/op	135 ns/op, 264 B/op
sb_sized	259 ns/op, 304 B/op	247 ns/op, 528 B/op
sb	302 ns/op, 512 B/op	316 ns/op, 888 B/op
concat	369 ns/op, 1224 B/op	408 ns/op, 1928 B/op
format	3855 ns/op, 1872 B/op	3647 ns/op, 2296 B/op

java.lang.String#equals

```
public boolean equals(Object anObject) {  
    if (this == anObject) {  
        return true;  
    }  
    if (anObject instanceof String) {  
        String aString = (String)anObject;  
        if (coder() == aString.coder()) {  
            return isLatin1() ? StringLatin1.equals(value, aString.value)  
                            : StringUTF16.equals(value, aString.value);  
        }  
    }  
    return false;  
}
```

java.lang.StringLatin1#equals

@HotSpotIntrinsicCandidate

```
public static boolean equals(byte[] value, byte[] other) {  
    if (value.length == other.length) {  
        for (int i = 0; i < value.length; i++) {  
            if (value[i] != other[i]) {  
                return false;  
            }  
        }  
    }  
    return true;  
}  
return false;  
}
```

	length=4	length=16	length=64	length=256
string_equals	7 ns/op	9 ns/op	8 ns/op	15 ns/op
hand_rolled	7 ns/op	14 ns/op	29 ns/op	97 ns/op

Brief History Lesson of String - Java 13

- **Fields:**
 - `private final byte[] value;`
 - `private final byte coder;`
 - `private int hash;`
 - `private boolean hashIsZero;`
- `hashCode()` avoids recalculation if `hash == 0`
- **Preview methods for text blocks - JEP 355**
 - `stripIndent()`
 - `translateEscapes()`
 - `formatted()`

JEP 355: Text Blocks

- Needs to be compiled and run with `--enable-preview`

- http://cr.openjdk.java.net/~jlaskey/Strings/TextBlocksGuide_v9.html

```
String html1d = "<html>\n" +  
    "    <body>\n" +  
    "        <p>Hello, world</p>\n" +  
    "    </body>\n" +  
"</html>\n";
```

```
String html2d = """"  
    <html>  
        <body>  
            <p>Hello, world</p>  
        </body>  
    </html>  
"""";
```

JEP 348: Compiler Intrinsics for Java SE APIs

- `String.format()` as fast as +
- Currently in Project Amber
 - Not targeted for a release yet

```
String appendBasic(String question, String answer1, String answer2) {  
    return "<h1>" + question + "</h1><ol><li>" + answer1 +  
        "</li><li>" + answer2 + "</li></ol>";  
}  
  
String appendFormat(String question, String answer1, String answer2) {  
    return String.format("<h1>%s</h1><ol><li>%s</li><li>%s</li></ol>",  
        question, answer1, answer2);  
}
```

StringAppenderBenchmark Mixed Parameters

	11.0.4	Amber (coming in Java 53*)
plus	61 ns/op 152 B/op	61 ns/op 152 B/op
format	2043 ns/op 1944 B/op	61 ns/op 152 B/op

- Running on MacBookPro 2.9 GHz Intel Core i9 1-6-2 machine
- Compile class with `-XDintrinsify=all`

* or later ...

Lessons from Today

- **Concatenate using `String.format()`**
 - Simpler to read and maintain
 - For performance critical, use `+` for now
 - In loops still use `StringBuilder.append()`
- **Avoid `intern()` in your code**
 - use String Deduplication or own cache instead
- **Strings since Java 9 use `byte[]`**
 - Might use less memory. Shorter maximum String if not Latin1

tinyurl.com/nisjug20